

FEATURES

- Patterns built by sequentially activating amber lamps; each lamp remains lit until the pattern is completed
- Available patterns include: left, right, center-out, and flashing warning
- Extrusion designed to block sunlight, increasing the warning effectiveness
- Separate controller is required to operate the SignalMaster™ unit. The full-featured controllers include: low-power mode to reduce amp draw for nighttime operation and fast mode that increases the “build” speed of the warning pattern.
- SignalMaster II models feature an integrated L-bracket control to activate three warning patterns: left, right, and flashing warning; a Brake/Turn/Tail override provides auxiliary warning when the unit is not in use.

REPLACEMENT PARTS

| | |
|------------|-----------------------------------------------------------|
| Z8573157 | Control for SignalMaster II units |
| Z140325-13 | 15-Position female connector for full-featured controller |



320772



331105

ORDER INFORMATION

LED SignalMaster Light Models

4-lamp units

| | |
|--------|----------------|
| 320742 | 20", 30' cable |
|--------|----------------|

6-lamp units

| | |
|--------|----------------|
| 320752 | 31", 15' cable |
| 320762 | 31", 30' cable |
| 320766 | 31", 60' cable |

8-lamp units

| | |
|--------|---------------------------|
| 320772 | 42", 15' cable |
| 320782 | 42", 30' cable |
| 320786 | 42", 60' cable |
| 320792 | 51", 30' cable |
| 320793 | 51", 50' cable |
| 321722 | 84", DOT strip, 35' cable |

SignalMaster Control Models

For use with 4-lamp, 6 lamp, or 8-lamp unit lights

| | |
|--------|--------------------------------------------------------|
| 330104 | Standard |
| 331105 | Full-featured (see page 70 for additional information) |

SignalMaster Complete System Models

8-lamp system

| | |
|--------|-------------------------------------------|
| 330312 | Includes: 320782 light and 331105 control |
|--------|-------------------------------------------|

SignalMaster II Light Models (includes control)

42", control, SIT/IT override

321702 15' cable

51", control, SIT/IT override

321712 35' cable

OPTIONS

| | |
|--------|--------------------------------|
| 320310 | Flush (vertical surface) mount |
| 320320 | Lightbar or rear deck mount |
| 320330 | System mount |
| 320340 | Universal mount |
| 320350 | Foot adapter mount |
| 320401 | Single LED module, upgrade kit |
| 320404 | 4-LED module, upgrade kit |
| 320406 | 6-LED module, upgrade kit |
| 320408 | 8-LED module, upgrade kit |

| SPECIFICATIONS | | | | |
|----------------|--------------------|------------------|-------------------|------------------|
| Voltage | 12 VDC | | | |
| Amp Draw | 0.3 per LED module | | | |
| SHIP WEIGHT | 4 LAMP | 6 LAMP | 42" - 8 LAMP | CONTROL |
| | 3.5 lbs (1.6 kg) | 6.0 lbs (2.7 kg) | 6.5 lbs (2.9 kg) | 1.0 lbs (0.5 kg) |
| | | | 51" - 8 LAMP | |
| | | | 9.7 lbs (4.4 kg) | |
| | | | 84" - 8 LAMP | |
| | | | 11.2 lbs (5.1 kg) | |
| DIMENSIONS | | | 42" - 8 LAMP | |
| Length | 19.5 in (495 mm) | 31.4 in (798 mm) | 41.8 in (1062 mm) | 5.1 in (130 mm) |
| Width | 3.3 in (84 mm) | 3.3 in (84 mm) | 3.3 in (84 mm) | 6.1 in (156 mm) |
| Height | 2.7 in (68 mm) | 2.7 in (68 mm) | 2.7 in (68 mm) | 1.4 in (35 mm) |
| | | | 51" - 8 LAMP | |
| Length | | | 50.9 in (1293 mm) | |
| Width | | | 3.3 in (84 mm) | |
| Height | | | 2.7 in (69 mm) | |
| | | | 84" - 8 LAMP | |
| Length | | | 84 in (2134 mm) | |
| Width | | | 3.3 in (84 mm) | |
| Height | | | 2.7 in (69 mm) | |

Notes:

- Mount brackets sold separately
- LED upgrade kits retrofit halogen SignalMaster lights built in July 1999 or later



320310



320320



320330



320340



320350