



## The SmartSiren® Platinum

Introducing the new SmartSiren Platinum from Federal Signal -- a smart step forward in user-friendly design, cutting-edge engineering, and effortless programmability.

Federal Signal's unique Convergence Network ties the vehicles warning system together with a simple "plug-n-play" connection between the SmartSiren Platinum and the lightbar.

An intuitively engineered remote control head puts at-a-glance command and control in your officer's hands and a simple PC interface makes it easy to program one vehicle or an entire fleet.

The new SmartSiren Platinum from Federal Signal. One more way Federal Signal technology is the smart choice.



## Features

### Convergence Network

- > The Federal Signal Convergence Network provides "plug-n-play" installation for all of Federal Signal serial communication lightbars.

### Configuration Software

- > The SmartSiren Platinum Configuration software gives the installer the ability to create, edit and distribute programming files within a fleet.

### Durable Remote Control Head

- > With an assured, tactile feel to its operation, the rugged three-position slide switch and control buttons provide ultimate control of your vehicles lighting and siren system.

### SignalMaster™ and Auxiliary Control

- > Fourteen programmable outputs and four inputs provide greater control and flexibility for controlling your vehicle's lighting system. The SignalMaster feature is standard for the SSP3000.

### Locking Relay Connectors

- > Locking Relay Connectors provide easy access to the 14 outputs and 4 inputs of the SmartSiren Platinum.

### Siren Diagnostics and 100/200-Watt Amplifier

- > Attention getting LEDs illuminate when auxiliary outputs/inputs are active to provide siren diagnostics and the amplifier can provide up to 200 watts of siren power.



Model #	Description	2009 List Price (US\$)
SSP3000	100/200W, programmable, convergence network enabled, diagnostic and full featured light and siren controller including SignalMaster	\$1,699.00
Z258B577B-03	Microphone, SmartSiren Platinum	\$56.75

Dimensions	Amplifier	Control Head
Height	4.40 in (11.18 cm)	3.26 in (8.28 cm)
Width	7.94 in (20.17 cm)	1.62 in (4.11 cm)
Length	7.58 in (19.25 cm)	6.81 in (17.30 cm)
Shipping Weight	6.8 lbs (3.09 kg)	
Input Voltage	11-16 VDC	
Operating Temp	-30°C to +65°C (relays at full power -30°C to 80°C, relay power 60%)	
Standby Draw	less than .5A	