



PA300R REMOTE MOUNTED CONTROL SIREN



Remotely going where no PA300 has gone before

The PA300R takes the functionality of the traditional PA300 siren and combines it with the flexibility of remote mounted controls. The PA300R is designed to provide either 100-watt or 200-watt output and features wail, yelp, air-horn, hi-low tones, manual, PA, and radio rebroadcast. When paired with high output Federal Signal speakers. The PA300R meets SAE J1849 and Class A requirements.

The PA300R is available with either one or two control head models. Siren control heads feature illuminated legends, large durable switches (push-buttons) for easy activation, and LED switch (button) indicators. Both models are equipped with a remotely mounted microphone with volume control. For a clean appearance, the microphone control head features a plug-in microphone with an easy accessible mic hook. All controls are design to sit flush with the vehicle's console.

Model 690014, as shown above, features two siren control heads and one microphone control unit. This model allows for custom vehicle installation and is designed to be operated in tandem by the driver and front passenger. Model 690015 comes equipped with one siren control head and one microphone control unit ideal for single person operation.

Installation is made easy with either PA300R model. All siren control units are connected using a standard RJ45 cable. The microphone control features true plug-and-play connections. The amplifier wiring harness is identical to the existing PA300. These features provide a clean, easy installation of the PA300R.

> Features

- 100/200-watt siren.
- Available in single and dual remote mounted control versions.
- Remote mounted noise-cancelling microphone and volume control.
- Siren features wail, yelp, air-horn, hi/low tones, and manual.
- Use with (1) or (2) 100-watt speakers or (1) 200-watt speaker.
- Control heads feature illuminated legends, LED indicators and large durable switches for easy control.

> Approvals

- SAE J1849
- Meets Class A (CAC)

> How to Order

Select Model

- 690014** PA300R, 100/200-watt, remote mounted control siren, (2) control heads, (1) noise cancelling microphone
- 690015** PA300R, 100/200-watt, remote mounted control siren, (1) control head, (1) noise cancelling microphone

Specifications			
Input Voltage	11 VDC - 15 VDC		
Standby Current	120 ma (typical)		
Operating Current	10A (max)		
Operating Temp.	-30°C to +65°C		
Physical Specifications			
	Amplifier	6-Button Control Head	Microphone Control
Height	3.0 in (7.6 cm)	2.3 in (5.9 cm)	3.8 in (9.5 cm)
Width	6.5 in (16.5 cm)	9.5 in (24.1 cm)	4.8 in (12.2 cm)
Depth	8.5 in (21.6 cm)	1.3 in (3.3 cm)	2.3 in (5.7 cm)
Ship Weight			
690014	7.5 lbs (3.4 kg)		
690015	7.0 lbs (3.2 kg)		



Model 690014 features two siren control heads and one microphone control unit. These controls are designed to work in tandem meaning operation may be controlled by either the driver or the passenger.