

FEATURES

- Patterns built by sequentially activating amber lamps; each lamp remains lit until the pattern is completed
- Available patterns include: left, right, center-out, and flashing warning
- Extrusion designed to block sunlight, increasing the warning effectiveness
- Separate controller is required to operate the SignalMaster™ unit. The full-featured controllers include: low-power mode to reduce amp draw for nighttime operation and fast mode that increases the “build” speed of the warning pattern.
- SignalMaster II models feature an integrated L-bracket control to activate three warning patterns: left, right, and flashing warning; a Brake/Turn/Tail override provides auxiliary warning when the unit is not in use
- Each module meets SAE J595 for flashing lights

REPLACEMENT PARTS

322502	12 VDC bulb
Z8573085	24 VDC bulb
322512-02	Lens, amber
Z8573157	Control for SignalMaster II units
Z8573180	Socket and reflector assembly
Z140325-13	15-Position female connector for full featured controller



320172



321112

ORDER INFORMATION

SignalMaster Light Models (purchase SignalMaster control separate)

19.5", 4-lamp unit

320142	30' cable
---------------	-----------

31.4", 6-lamp units

320162	15' cable
320612	30' cable

41.8", 8-lamp units

320172	15' cable
320172-24V	24 VDC, 15' cable
320182	30' cable
320192	50' cable
320602	84", DOT strip, 35' cable

SignalMaster Control Models

For use with any 4-lamp, 6-lamp, or 8-lamp unit lights

330104	Standard
331105	Full-featured

SignalMaster Complete System Models

4-lamp system

323142	(2) 320142 lights, (1) 330104 control, and (2) 320310 mounts
---------------	--------------------------------------------------------------

6-lamp system

330302	(1) 320612 light and (1) 331105 control
---------------	-----------------------------------------

8-lamp systems

322112	(1) 320182 light and (1) 331105 control
322122	(1) 320192 light and (1) 331105 control
322612	(1) 51" light with (1) 30' cable and (1) 331105 control
322132	(1) 320182 light, (1) 331105 control, and (1) 320320 mount

SignalMaster II Light Models (includes integrated control)

42", control, SIT/IT override

321102 15' cable

51", control, SIT/IT override

321112 35' cable

OPTIONS

320310 Flush (vertical surface) mount

320320 Lightbar or rear deck mount

320330 System mount

320340 Universal mount

320350 Foot adapter mount

320400 50' cable kit

Note: Mount brackets sold separately

SPECIFICATIONS				
Voltage	12 VDC			
Amp Draw	2.1 per lamp			
SHIP WEIGHT	4 LAMP	6 LAMP	42" - 8 LAMP	CONTROL
	3.5 lbs (1.6 kg)	6.0 lbs (2.7 kg)	6.5 lbs (2.9 kg)	1.0 lbs (0.5 kg)
			51" - 8 LAMP	
			9.7 lbs (4.4 kg)	
			84" - 8 LAMP	
			11.2 lbs (5.1 kg)	
DIMENSIONS			42" - 8 LAMP	
Length	19.5 in (495 mm)	31.4 in (798 mm)	41.8 in (1062 mm)	5.1 in (130 mm)
Width	3.3 in (84 mm)	3.3 in (84 mm)	3.3 in (84 mm)	6.1 in (156 mm)
Height	2.7 in (68 mm)	2.7 in (68 mm)	2.7 in (68 mm)	1.4 in (35 mm)
			51" - 8 LAMP	
Length			50.9 in (1293 mm)	
Width			3.3 in (84 mm)	
Height			2.7 in (69 mm)	
			84" - 8 LAMP	
Length			84 in (2134 mm)	
Width			3.3 in (84 mm)	
Height			2.7 in (69 mm)	



330104



331105



320310



320320



320330



320340



320400



320350