

February 27, 2020

Obsolete Product Notice:

Models PMMFL and PMMST Multicolor Panel Mount LED Beacons

Models PMMFL and PMMST Multicolor Panel Mount LED Beacons have been discontinued. We currently have limited stock on hand. Once inventory is depleted, these models are no longer available.

Model	Obsolescence Status
PMMFL-012-024	QTY 31 available as of 2/27/20; once inventory is depleted model will be obsolete
PMMFL-048-240	QTY 37 available as of 2/27/20; once inventory is depleted model will be obsolete
PMMST-012-024	QTY 35 available as of 2/27/20; once inventory is depleted model will be obsolete
PMMST-012-024C	QTY 20 available as of 2/27/20; once inventory is depleted model will be obsolete
PMMST-048-240	QTY 45 available as of 2/25/20; once inventory is depleted model will be obsolete

Recommended Alternatives:

For applications that require **panel mount** units, the recommended alternatives are the PMLMP/PMLST.

<p>PMLMP and PMLST Panel Mount Multifunctional LED Beacons</p> 	<p>12-24VAC/DC or 48-240VAC Single color beacons available in six colors Steady (PMLST) or multi-pattern (PMLMP) 50,000 hour LED 360 degrees light-diffusing design Type 4X, IP66 enclosure IP69K compliant CE Certified UL and cUL Listed</p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

For applications that require **multicolor** units, the recommended alternatives are the SLM1400/SLM1450.

<p>SLM1400 and SLM1450 StreamLine® Modular Multicolor Low Profile LED Beacons</p> 	<p>12-24VAC/DC or 120-240VAC Eight colors per channel Five flash patterns per channel 50,000 hour LED Seven mounting base options (sold separately) Type 4X, IP66 enclosure; IP69K compliant CE Certified UL and cUL Listed</p>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

For additional product information and specifications on the recommended alternatives, use the links above or visit www.fedsig.com. Feel free to contact your Regional Sales Manager, Inside Sales or Customer Support at signalsupport@fedsig.com or +1 708-534-4756 with any additional questions.