

SignalTech_® LED Lights

Exterior Perimeter Lights



FEATURES

- 4" round and 6" oval LED lights
- 2" and 2.5" side marker/clearance LED lights
- Kits includes LED light, rubber mount grommet, and sealed wired harness
- . 1.5" indicator light in Red flashing and steady
- 1-up, 2-up, and 3-up mounting boxes available for 6" oval lights
- Three-year warranty

APPROVALS

Flashing Models

- SAE J595 Class 1
- CCR Title 13 (select models)

STT/Turn/Backup/Marker Light Models

- FMVSS 108 compliant
- SAE J593 (Backup)
- SAE J1398 (Stop)

SignalTech® LED Light Series

SignalTech® LED lights are designed for emergency vehicle specifications and engineered to meet the demands of various work trucks, including construction, municipal, utility, and tow and recovery. SignalTech LED lights feature a high-impact resistant polycarbonate housing and feature LED technology to reduce maintenance costs.

Flashing LED Light Kits

Each LED light head produces an attention-getting warning signal that meets SAE J593 Class 1. The flashing LED light heads are offered in 4-inch round and 6-inch oval kits. The kits come equipped with a rubber grommet and sealed wire harness.

S/T/T, Turn, and Backup LED Light Kits

Complement your LED light kits with SignalTech S/T/T (Stop/Tail/Turn), turn and backup LED light kits. All LED light kits feature a triple-sealed plug that allows for easy installation to existing backup, S-T-T and turn circuits. The LED lights operate at 12 or 24 Vdc and are voltage regulated for consistent light output. SignalTech lights comply with DOT requirements.

Side Marker/Clearance Lights

SignalTech Side Marker/Clearance lights complement flashing or S/T/T lights. These lights available in 2-inch and 2.5-inch round models and operate at 12 Vdc.



HOW TO ORDER

RANDOM FLASHING LED	LIGHT KITS (71 QUAD FPM)	
607123-02SB	4-inch round, PAR36, Amp harness, Amber	
607123-03SB	4-inch round, PAR36. Amp harness, Blue	
607123-04SB	4-inch round, PAR36, Amp harness, Red	
607123-05SB	4-inch round, PAR36, Amp harness, White	
607101-02SB	6-inch oval, Amp harness, Amber	
607101-03SB	6-inch oval, Amp harness, Blue	
607101-04SB	6-inch oval, Amp harness, Red	
607101-05SB	6-inch oval, Amp harness, White	
S/T/T, TURN, AND BACKUP LED LIGHT KITS		
607100-04SB	4-inch round, stop/tail/turn light, Amp harness, Red	
607102-02SB	4-inch round, turn light, Amp harness, Amber	
607124-05SB	4-inch round, backup light, Amp harness, White	
607124-05SB-DEU	4-inch round, backup light, Amp harness, weather tight connector, White	
607105-04SB	6-inch oval, stop/tail/turn light, Amp harness, Red	
607106-02SB	6-inch oval, turn light, Amp harness, Amber	
607125-05SB	6-inch oval, backup light, Amp harness, White	
607130-45SB	6-inch oval, combo stop/tail/turn and backup light, Red and White	
SIDE MARKER/CLEARANCE LED LIGHT KIT MODELS, 12 VDC		
607120-02SB	2.5-inch round, PL10 harness, Amber	
607120-04SB	2.5-inch round, PL10 harness, Red	
607120-02SB-AMP	2.5-inch round, Amp harness, Amber	
607120-04SB-AMP	2.5-inch round, Amp harness, Red	
607119-02SB	2-inch round, Amp harness, Amber	
607119-04SB	2-inch round, Amp harness, Red	
INDICATOR LIGHT		
607121-04SB	Indicator light, 1.5-inch round flashing and steady, Red	

ACCESSORIES AND KITS	
605523-02SB	4-inch round flashing LED light head, Amber; -03SB(Blue); -04SB(Red)
605501-02SB	6-inch oval flashing LED light head, Amber; -04SB(Red); -03SB(Blue)
605520SB	Kit, rubber mounting grommet, 4-inch round
605510SB	Kit, rubber mounting grommet, 4-inch round
605500SB	Sealed wire harness for flashing LED light heads
607109SB	Sealed wire harness for S/T/T and Turn LED light heads
605530SB	2.5-inch round mounting grommet
305101SSG	1-up pair mounting boxes for 6-inch oval lights, matte Black
305102SSG	2-up pair mounting boxes for 6-inch oval lights, matte Black
305103SSG	3-up pair mounting boxes for 6-inch oval lights, matte Black
SPECIFICATIONS	LED Color A B R W A B R C
SPECIFICATIONS	
SPECIFICATIONS	
	A B R W A B R C
VOLTAGE	A B R W A B R C
VOLTAGE OPERATING TEMP	12/24 Vdc -22° to 149° F (-30° to + 65° C) 0.3 A @ 12 Vdc
VOLTAGE OPERATING TEMP CURRENT DRAW	12/24 Vdc -22° to 149° F (-30° to + 65° C) 0.3 A @ 12 Vdc
VOLTAGE OPERATING TEMP CURRENT DRAW PHYSICAL SPECIFICAT	12/24 Vdc -22° to 149° F (-30° to + 65° C) 0.3 A @ 12 Vdc
VOLTAGE OPERATING TEMP CURRENT DRAW PHYSICAL SPECIFICAT 2" ROUND (DIA. X D.)	12/24 Vdc -22° to 149° F (-30° to + 65° C) 0.3 A @ 12 Vdc 10NS 2.0 in x 0.8 in (5.1 cm x 0.2 cm)
VOLTAGE OPERATING TEMP CURRENT DRAW PHYSICAL SPECIFICAT 2" ROUND (DIA. X D.) 2.5" ROUND (DIA. X D.)	12/24 Vdc -22° to 149° F (-30° to + 65° C) 0.3 A @ 12 Vdc 10NS 2.0 in x 0.8 in (5.1 cm x 0.2 cm) 2.5 in x 0.8 in (6.4 cm x 0.2 cm)
VOLTAGE OPERATING TEMP CURRENT DRAW PHYSICAL SPECIFICAT 2" ROUND (DIA. X D.) 2.5" ROUND (DIA. X D.) 4" ROUND (DIA. X D.)	12/24 Vdc -22° to 149° F [-30° to +65° C] 0.3 A @ 12 Vdc 10NS 2.0 in x 0.8 in [5.1 cm x 0.2 cm] 2.5 in x 0.8 in [6.4 cm x 0.2 cm] 4.3 in x 1.8 in [109 cm x 4.5 cm] 6.4 in x 1.9 in x 2.4 in
VOLTAGE OPERATING TEMP CURRENT DRAW PHYSICAL SPECIFICAT 2" ROUND (DIA. X D.) 2.5" ROUND (DIA. X D.) 4" ROUND (DIA. X D.) 6.5" OVAL (L X W X H)	12/24 Vdc -22° to 149° F [-30° to +65° C] 0.3 A @ 12 Vdc 10NS 2.0 in x 0.8 in [5.1 cm x 0.2 cm] 2.5 in x 0.8 in [6.4 cm x 0.2 cm] 4.3 in x 1.8 in [109 cm x 4.5 cm] 6.4 in x 1.9 in x 2.4 in [16.4 cm x 4.8 cm x 6.0 cm]
VOLTAGE OPERATING TEMP CURRENT DRAW PHYSICAL SPECIFICAT 2" ROUND (DIA. X D.) 2.5" ROUND (DIA. X D.) 4" ROUND (DIA. X D.) 6.5" OVAL (L X W X H) SHIP WEIGHT	12/24 Vdc -22° to 149° F [-30° to +65° C] 0.3 A @ 12 Vdc 10NS 2.0 in x 0.8 in [5.1 cm x 0.2 cm] 2.5 in x 0.8 in [6.4 cm x 0.2 cm] 4.3 in x 1.8 in (109 cm x 4.5 cm) 6.4 in x 1.9 in x 2.4 in [16.4 cm x 4.8 cm x 6.0 cm]

