

LED Traffic Clearing Light

Exterior Perimeter Light



FEATURES

- Delivers 250+ feet of direct warning light
- Available in 9x7 and 6x4 sizes
- Available with Amber, Blue, Green, Red, and White LEDs
- Available with Amber, Clear, and Red lens
- 6x4 model available as an option in the Navigator® light bar
- Optional Chrome Bezels available
- Five-year warranty

Alert Drivers Faster

Federal Signal's LED Traffic Clearing Light (TCL) is designed to bring attention to drivers as a fire apparatus or ambulance is approaching from the rear of their vehicle. The LED TCL's optics and unique sequence of flash patterns direct light to the driver's rear-view mirror, warning them of the emergency vehicle.

LED TCL and perimeter warning lights work together to help warn roadway traffic. While perimeter lights provide 360-degree of warning light around the emergency vehicle, the LED TCL produces 250+ feet of directional light to the front of the emergency vehicle.

LED TCL Models

LED TCL is available in 6x4 and 9x7 standard models. Models are available in Amber, Blue, Green, Red, and White LEDs. The LED TCL 6x4 is sold in pairs and is available as an option for Federal Signal's Navigator® light bar.

APPROVALS

- GSA KKK-A-1822F (LEDTCL97C-W flash pattern 7)



Navigator® light bar shown with (2) 6x4 LED TCL models

HOW TO ORDER

LED Color Lens Color
A B G R W A C R

LED TRAFFIC CLEARING LIGHT, 6X4 (PAIR)

LEDTCL64A-A	Amber lens, Amber LED
LEDTCL64C-A	Clear lens, Amber LED
LEDTCL64C-B	Clear lens, Blue LED
LEDTCL64C-G	Clear lens, Green LED
LEDTCL64C-R	Clear lens, Red LED
LEDTCL64C-W	Clear lens, White LED
LEDTCL64R-R	Red lens, Red LED

LED TRAFFIC CLEARING LIGHT, 9X7

LEDTCL97A-A	Amber lens, Amber LED
LEDTCL97C-A	Clear lens, Amber LED
LEDTCL97C-B	Clear lens, Blue LED
LEDTCL97C-G	Clear lens, Green LED
LEDTCL97C-R	Clear lens, Red LED
LEDTCL97C-W	Clear lens, White LED
LEDTCL97R-R	Red lens, Red LED

ACCESSORIES

QL64MC	6x4 trim bezel, Chrome with gasket
QL97MC	9x7 trim bezel, Chrome with gasket

SPECIFICATIONS


	6x4	9x7
CURRENT DRAW	3.0 A/1.5 A	7.0 A
OPERATING VOLTAGE	12/24 Vdc	12 Vdc
OPERATING TEMP	-40° to 176° F (-40° to 80° C)	
PHYSICAL SPECIFICATIONS		
LENGTH	6.6 in (16.7 cm)	9.2 in (23.3 cm)
WIDTH	1.7 in (4.2 cm)	1.7 in (4.2 cm)
HEIGHT	4.2 in (10.5 cm)	7.2 in (18.1 cm)
SHIP WEIGHT		
	0.8 lb (0.4 kg)	1.8 lb (0.8 kg)



LEDTCL97A-A



LEDTCL97C-B



LEDTCL97C-G



LEDTCL97R-R



LEDTCL97C-W



LEDTCL64A-A



LEDTCL64C-B



LEDTCL64C-G



LEDTCL64C-R



LEDTCL64C-W

