

Firebolt® Class 2 LED

Beacon



FEATURES

- (15) selectable flash patterns
- Built-in permanent 1/2-inch pipe mount base
- Magnet mount models with accessory plug available
- Polycarbonate base and dome
- Multi-voltage, 12/72 Vdc
- Five-year warranty

APPROVAL

- SAE J845 Class 2

A Superior Warning Signal

Firebolt® LED beacon features an innovative Federal Signal designed LED emitter that produces a superior warning signal to promote work zone safety. The LED technology in the Firebolt LED allows for a minimal amp draw of less than 0.5 A while meeting Class 2 standards.

Power Select™ Feature

Firebolt LED offers (15) user selectable flash patterns through Federal Signal's patented Power Select™ feature. The Power Select allows users to scroll through flash patterns by simply following a sequence of applying power to the unit 3 times in a row, putting the beacon into programming mode.

Built for Versatility and Durability

Designed to meet the demands of various work zones, including snowplows, forklifts, utility trucks and construction vehicles, the Firebolt LED is made of a shatterproof, polycarbonate dome and base and includes an o-ring to help protect against moisture. Firebolt LED has a built-in permanent 1/2-inch pipe mount base. Magnet mount models with accessory plugs are also available.



Magnetic mount accessory plug option is available



Built-in permanent 1/2-inch pipe mount



Shatterproof dome and base with o-ring protection against moisture

HOW TO ORDER

LED Color: **A** **B** **R** **W** Dome Color: **A** **B** **C** **R**

FIREBOLT LED, CLASS 2, PERMANENT /1/2-INCH PIPE MOUNT

220250-02	Amber LEDs, Amber dome
220250-03	Blue LEDs, Blue dome
220250-04	Red LEDs, Red dome
220250-05	White LEDs, Clear dome

MAGNET MOUNT, ACCESSORY PLUG

220260-02	Amber LEDs, Amber dome
220260-03	Blue LEDs, Blue dome
220260-04	Red LEDs, Red dome
220260-05	White LEDs, Clear dome

ACCESSORIES AND KITS

210539	L-mounting bracket
210728	Kit, magnetic mount with accessory plug
211676	Dome guard assembly, Chrome

SPECIFICATIONS

	PERMANENT MOUNT	MAGNET MOUNT
OPERATING VOLTAGE	12/72 Vdc	
CURRENT DRAW	<0.5A @ 12 Vdc <0.25A @ 24 Vdc <0.15A @ 48 Vdc <0.1A @ 72 Vdc	
FLASH PATTERNS	15	
OPERATING TEMP	-22° to +149° F (-30° to +65° C)	
PHYSICAL SPECIFICATIONS		
DIAMETER	5.1 in (12.9 cm)	
HEIGHT	3.6 in (9.2 cm)	4.0 in (10.2 cm)
SHIP WEIGHT	0.9 lb (0.4 kg)	1.4 lb (0.6 kg)

