

1 **SUPPLEMENTARY EC - TYPE EXAMINATION CERTIFICATE**

2 **Equipment or Protective System Intended for use in Potentially Explosive Atmospheres  
Directive 94/9/EC**

3 Supplementary EC - Type Examination Certificate Number: **Baseefa07ATEX0150/2**

4 Equipment or Protective System: **Series 2000 Beacon**

5 Manufacturer: **Federal Signal Corporation**

6 Address: **2645 Federal Signal Drive, University Park, Illinois 60484, USA**

7 This supplementary certificate extends EC – Type Examination Certificate No. **Baseefa07ATEX0150** to apply to equipment or protective systems designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.

8 Item 9 of the original Certificate is replaced by “Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

**EN 60079-0: 2012**

**EN 60079-1: 2007**

**EN 60079-7: 2007**

**EN 60079-31: 2009**

except in respect of those requirements listed at item 18 of the Schedule.”

9 The marking of the equipment has changed from the original Certificate and shall include the following:

**⊕ II 2GD – see schedule for amended certification marking**

This certificate shall be held with the original certificate.

Baseefa Customer Reference No. **5121**

Project File No. **13/0116**

This document is issued by the Company subject to its General Conditions for Certification Services accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and the Supplementary Terms and Conditions accessible at <http://www.baseefa.com/terms-and-conditions.asp>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company’s findings at the time of its intervention only and within the limits of Client’s instructions, if any. It does not necessarily indicate that the equipment may be used in particular industries or circumstances. The Company’s sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, schedule included, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**SGS Baseefa Limited**



Rockhead Business Park, Staden Lane,  
Buxton, Derbyshire SK17 9RZ

Telephone +44 (0) 1298 766600 Fax +44 (0) 1298 766601

e-mail [info@baseefa.com](mailto:info@baseefa.com) web site [www.baseefa.com](http://www.baseefa.com)

Registered in England No. 4305578.

Registered address: Rossmore Business Park, Ellesmere Port, Cheshire, CH65 3EN

  
**P. S. SINCLAIR**   
GENERAL MANAGER

On behalf of SGS Baseefa Limited

13

## Schedule

14

Certificate Number Baseefa07ATEX0150/2

### 15 Description of the variation to the Equipment or Protective System

#### Variation 3.1

The equipment covered by this certificate has been reviewed against the additional design and test requirements of EN 60079-0: 2012, EN 60079-1: 2007 and EN 60079-31: 2009 (superseding EN 61241 for dust hazards), and compliance is confirmed.

The units with Xenon or Fluorescent lamps may be marked with the following amended coding :-

⊕ II 2GD Ex d IIB T4 Gb, Ex tb IIIB T135°C Db (-40°C ≤Ta ≤+70°C) IP66

or if fitted with the Increased Safety terminal box :-

⊕ II 2GD Ex de IIB T4 Gb, Ex tb IIIB T135°C Db (-40°C ≤Ta ≤+70°C) IP66

The units with LED lamps may be marked with the following amended coding :-

⊕ II 2GD Ex d IIB T6 Gb, Ex tb IIIB T85°C Db (-40°C ≤Ta ≤+55°C) IP66

or if fitted with the Increased Safety terminal box :-

⊕ II 2GD Ex de IIB T6 Gb, Ex tb IIIB T85°C Db (-40°C ≤Ta ≤+55°C) IP66

### 16 Report Number

Baseefa Report No. GB/BAS/ExTR13.0153/00

### 17 Specific Conditions of Use

None

### 18 Essential Health and Safety Requirements

Compliance with the Essential Health and Safety Requirements is not affected by this variation.

### 19 Drawings and Documents

| Number  | Issue | Date   | Description                                  |
|---------|-------|--------|--|
| 259110A | A7    | 6/7/13 | General Arrangement, 2000 Series Beacon      |
| 259124A | A2    | 6/7/13 | Certification Labels, 2000 Series Beacon     |
| 259205A | A2    | 6/7/13 | Certification Labels, 2000 Series LED Beacon |

These drawings are common to, and held with, IECEX BAS 07.0038



1 **EC - TYPE EXAMINATION CERTIFICATE**

2 **Equipment or Protective System Intended for use in Potentially Explosive Atmospheres**  
3 **Directive 94/9/EC**

3 EC - Type Examination Certificate Number: **Baseefa07ATEX0150**

4 Equipment or Protective System: **Series 2000 Beacon**

5 Manufacturer: **Federal Signal Corporation**

6 Address: **Federal Signal Drive, University Park, Illinois 60466-3195, USA**

7 This equipment or protective system and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

8 Baseefa (2001) Ltd., Notified Body number 1180, in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Report No. **GB/BAS/ExTR07.0081/00**

9 Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

**EN 60079-0:2006, EN 60079-1:2004, EN 60079-7:2006, EN 61241-0:2006, EN 61241-1:2004**

except in respect of those requirements listed at item 18 of the Schedule.

10 If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.

11 This EC - TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified equipment or protective system. Further requirements of the Directive apply to the manufacturing process and supply of this equipment or protective system. These are not covered by this certificate.

12 The marking of the equipment or protective system shall include the following :

**Ex II 2GD see schedule for certification marking**

This certificate may only be reproduced in its entirety, without any change, schedule included.


Baseefa Customer Reference No. 5121

Project File No. 06/1037

This certificate is granted subject to the general terms and conditions of Baseefa (2001) Ltd. It does not necessarily indicate that the equipment may be used in particular industries or circumstances.

**Baseefa**

Rockhead Business Park, Staden Lane,  
Buxton, Derbyshire SK17 9RZ  
Telephone +44 (0) 1298 766600 Fax +44 (0) 1298 766601  
e-mail [info@baseefa.com](mailto:info@baseefa.com) web site [www.baseefa.com](http://www.baseefa.com)  
Baseefa is a trading name of Baseefa (2001) Ltd  
Registered in England No. 4305578 at the above address

  
P. R. S. SINCLAIR  
DIRECTOR  
On behalf of  
Baseefa (2001) Ltd.



13

## Schedule

14

### Certificate Number Baseefa07ATEX0150

#### 15 Description of Equipment or Protective System

The 2000 Series Beacon is rated at up to 240V a.c. and comprises a base and cover from aluminium alloy. The cover is provided with a cemented wellglass, the cover is secured to the base via four grade A2-70 stainless steel screws.

The beacon may be provided with up to four Xenon Lamps up to a maximum power of 60VA which flash at a maximum rate of 95 flashes a minute, or up to four fluorescent lamps up to a maximum power of 36W, or light emitting diodes (LEDs) rated at up to 9W; in this form the unit is Exd.

Alternatively the base may be drilled and fitted with line bushings terminated within an increased safety terminal box attached to the side of the beacon, which also contains increased safety terminals; in this form the unit is Exde.

In the above forms the Series 2000 Beacon may be marked:-

Ex d IIB T4 ExtD A21 IP66 T135°C (- 40°C ≤ ta ≤ + 70°C) with Xenon or Fluorescent lamps fitted, or

Ex de IIB T4 ExtD A21 IP66 T135°C (- 40°C ≤ ta ≤ + 70°C) when additionally fitted with increased safety terminal box, or

Ex d IIB T6 ExtD A21 IP66 T85°C (- 40°C ≤ ta ≤ + 55°C) with LED lamps fitted, or

Ex de IIB T6 ExtD A21 IP66 T85°C (- 40°C ≤ ta ≤ + 55°C) when additionally fitted with the increased safety terminal box.

To obviate the risk from internal hotspots associated with the Series 2000 Beacon the enclosure must not be opened even when isolated, when a flammable atmosphere is present. A label stating this information is fitted externally to each and every enclosure.

Cable entry holes are provided as specified on the certified drawings for the accommodation of flameproof cable entry devices, with or without the interposition of a flameproof thread adapter. Unused entries are to be fitted with suitable certified flameproof stopping plugs.

The cable entry devices, thread adapters and stopping plugs shall be suitable for the equipment, the cable and the conditions of use and shall be certified as Equipment (not a Component) under an EC-Type Examination Certificate to Directive 94/9/EC.

When used in an explosive dust atmosphere the cable entry devices shall maintain the ingress protection of the enclosure

Internal and external earthing facilities are provided.

#### 16 Report Number

Baseefa Certification Report GB/BAS/ExTR07.0081/00

#### 17 Special Conditions for Safe Use

None

#### 18 Essential Health and Safety Requirements

All relevant Essential Health and Safety Requirements are covered by the standards listed at item 9.

#### 19 Drawings and Documents

| Number  | Issue | Date    | Description                            |
|---------|-------|---------|--|
| 259110A | A4    | 6/21/07 | General Arrangement 2000 Series Beacon |
| 259111A | A     | 3/17/05 | General Arrangement Xenon Twin Lamp    |



---

| <b>Number</b> | <b>Issue</b> | <b>Date</b> | <b>Description</b>                               |
|---------------|--------------|-------------|--|
| 259112A       | A            | 3/17/05     | General Arrangement Xenon Four Lamp              |
| 259113A       | A            | 3/17/05     | General Arrangement Fluorescent Twin Lamp        |
| 259114A       | A            | 3/17/05     | General Arrangement Fluorescent Four Lamp        |
| 259206A       | A            | 11/29/06    | General Arrangement LED Units                    |
| 259115A       | A            | 3/17/05     | Base Casting Beacon Series 2000                  |
| 259116A       | A1           | 4/18/07     | Base Machining Detail Beacon Series 2000         |
| 259117A       | A            | 3/16/05     | Cover Casting Beacon Series 2000                 |
| 259118A       | A            | 3/16/05     | Cover Machining Detail Beacon series 2000        |
| 259119A       | A            | 3/16/05     | Clamping Ring Series 2000 Beacon                 |
| 259120A       | A1           | 6/21/07     | Terminal Box Base Series 2000 Beacon             |
| 259121A       | A1           | 6/21/07     | Terminal Box Cover Series 2000 Beacon            |
| 259122A       | A1           | 4/27/07     | Wellglass Cementing Procedure Series 2000 Beacon |
| 259123A       | A1           | 6/20/07     | Label Warning Beacon Series 2000                 |
| 259124A       | A1           | 6/19/07     | Certification Labels Series 2000 Beacon          |
| 259205A       | A1           | 6/19/07     | Certification Labels 2000 LED Beacon             |

These drawings are common to BAS IECEx 07.0150 and are controlled on and held with GB/BAS/ExTR 07.0081/00