



Model SLM600 shown with mounting base options (ordered separately)

► Model SLM600









# StreamLine® Modular Multifunctional High Output LED Combination Audible/Visual Signals

Model SLM600 is a multifunctional LED beacon and sounder combination developed with a multiple-input technology that allows three separate levels of alarm, controllable via wiring selection. This unit offers multiple combinations, including independent visual signal, independent audible tone, or a combined audible tone and visual signal.

The SLM600 offers three flash patterns (3x strobe, fade, and steady) and the option of no visual effect. There are 64 unique tones to select from across two switches (32 tones per switch). The volume of the selected tone is adjustable between 99-115 dBA at 1 m at three output levels (high, medium, low) through an integrated button.

Channel 1 includes a visual signal only. Channel 2 combines an audible tone from switch A to the chosen flash pattern. Channel 3 combines an audible tone from switch B to the chosen flash pattern. Channel 2 and 3 allow the option of audible tone only/no visual effect by cycling through the flash patterns using the integrated button until the visual effect turns off.

The SLM600 enclosure is made from a self-extinguishing polycarbonate material with high impact and UV resistance.

			LENS COLOR OPTIONS     
--	--	--	---

## FEATURES

- Compatible with 12-24 Vac/dc or 120-240 Vac\*
- PLC compatible with PNP or NPN connections
- 3 Channels included:
  - 1: Visual signal only
  - 2: Visual signal + tone 1
  - 3: Visual signal + tone 2
- Option to have independent audible tone
- 100,000-hour LED
- Five LED lamp/lens colors: Amber, Blue, Clear, Green, and Red
- Three flash patterns: 3x strobe, fade, and steady
- 64 tone options at three adjustable levels
- Seven mounting base options
- Type 3R, IP65 enclosure
- CE and UKCA compliant
- UL and cUL Listed

\* Voltage is dependent on selected base (sold separately)

MODEL	VOLTAGE	FLASH RATE/MINUTE (FLASH MODE)	DECIBELS (MIN.-MAX.)	
			10'	1 m
<b>SLM600*</b>	12-24 Vac/dc or 120-240 Vac	85 (+/-10)	89-105	99-115


\* Indicates color: (A) Amber, (B) Blue, (C) Clear, (G) Green, or (R) Red

MAXIMUM OPERATING CURRENT (mA)					
12 Vdc	24 Vdc	12 Vac	24 Vac	120 Vac	240 Vac
400	300	800	700	300	200

### Weight (unit(s) + base = total weight)

SLM600	VOLTAGE	SHALLOW BASE	DEEP BASE	WALL MOUNT	PIPE MOUNT	TWIN WALL MOUNT
19.05 oz	12-24 Vac/dc	2.12 oz 0.06 kg	4.23 oz 0.12 kg	6.70 oz 0.19 kg	5.29 oz 0.15 kg	9.17 oz 0.26 kg
0.54 kg	120-240 Vac	—	6.0 oz 0.17 kg	8.47 oz 0.24 kg	6.70 oz 0.19 kg	12.35 oz 0.35 kg

# StreamLine® Modular Multifunctional High Output LED Combination Audible/Visual Signals (SLM600)



## SPECIFICATIONS











Lamp Life: 100,000 Hours  
 Light Source: LED  
 Operating Temperature Range: -40° to 131°F ( -40° to 55°C)

### Mounting Base Options

Mounting bases are rated Type 4X. Final product rating is determined by top module. In combination with SLM600 and the included/required retaining ring (SLM-RR), the unit is Type 3R, IP65.

## HOW TO ORDER

- Specify model number SLM600 and color
- Specify required mounting base (see chart)
- Optional dome guard:  
 For shallow mounting base (SLMDG2)  
 For deep mounting base (SLMDG3)
- Accessories for Twin and Wall Mount Bases:  
 Cable Gland, M20, Gray, 2 Pack (K77700416)  
 Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base:  
 1-inch NPT Adapter (SLMNPT1)  
 1/2-inch NPT Adapter (SLMNPT2)

	Model Number	Base Color	Voltage	
 Shallow Base	SLMBS-012-024GY	Gray	12-24 Vac/dc	
	SLMBS-012-024R	Red	12-24 Vac/dc	
 Deep Base	SLMBD-012-024GY	Gray	12-24 Vac/dc	
	SLMBD-012-024R	Red	12-24 Vac/dc	
	SLMBD-120-240GY	Gray	120-240 Vac	
 Wall Mount	SLMBW-012-024GY	Gray	12-24 Vac/dc	
	SLMBW-120-240GY	Gray	120-240 Vac	
 Pipe Mount	SLMBP-012-024GY	Gray	12-24 Vac/dc	
	SLMBP-120-240GY	Gray	120-240 Vac	
 Twin Wall Mount	SLMBT-012-024GY	Gray	12-24 Vac/dc	
	SLMBT-120-240GY	Gray	120-240 Vac	