

- Models AD-26, AD-27, AD-56 and AD-57

Atkinson Dynamics Wall Mount Intercoms




Designed for single-channel, two-way indoor and outdoor communication applications, Wall-Mount Intercoms feature integrated volume control, TALK/LISTEN switch, corrosion resistant cast aluminum housing with rugged powder coat finish (Type 4X enclosure), reliable 25-watt speaker, and balanced line output. These heavy duty units are UL and cUL listed, CSA Certified and Marine rated; and available in 12VDC, 24VDC, 120VAC, or 240VAC 50/60Hz models.

FEATURES

- Available in 12VDC, 24VDC, 120VAC, or 240VAC 50/60Hz
- Heavy-duty industrial intercom for indoor/outdoor application
- Single-channel, two-way communications
- Integrated volume control and Talk/Listen switch
- Balanced line output
- 25 watt speaker
- Cast aluminum housing with rugged powder coat finish
- Conformal coated PCB
- Type 4X enclosure
- Marine Listed
- UL and cUL Listed

| MODEL | VOLTAGE | OPERATING CURRENT | STANDBY CURRENT | FREQUENCY RESPONSE |
|--------------|----------------|-------------------|-----------------|--------------------|
| AD-26 | 12VDC | 1.47 A | 100 mA | 320Hz - 8.0Khz |
| AD-27 | 120VAC 50/60Hz | 240 mA | 83 mA | 320Hz - 8.0Khz |
| AD-56 | 24VDC | 1.65 A | 100 mA | 320Hz - 8.0Khz |
| AD-57 | 240VAC 50/60Hz | 127 mA | 83 mA | 320Hz - 8.0Khz |

Atkinson Dynamics Wall Mount Intercoms (AD-26, AD-27, AD-56 and AD-57)



SPECIFICATIONS

| | | |
|-----------------------|----------------|---------------|
| Speaker Rating | | 25 watt |
| Operating Temperature | -31°F to 150°F | -35°C to 66°C |
| Net Weight | 9 lbs | 4.08 kg |
| Shipping Weight: | | |
| AD-26 | 10.0 lbs | 4.54 kg |
| AD-27 | 10.7 lbs | 4.85 kg |
| AD-56 | 10.0 lbs | 4.54 kg |
| AD-57 | 10.7 lbs | 4.85 kg |
| Height | 9.88" | 251.0 mm |
| Width | 6.50" | 165.1 mm |
| Depth | 5.03" | 127.8 mm |

HOW TO ORDER

Step 1: Specify Base Model

- AD-26** (12VDC, Wall Mount Intercom)
- AD-27** (120VAC, Wall Mount Intercom)
- AD-56** (24VDC, Wall Mount Intercom)
- AD-57** (240VAC, Wall Mount Intercom)

Step 2: Add Optional Features

Example Part Number: AD-27A

OPTIONAL FEATURES

Note: Not all optional features are available for every model. Please consult factory to confirm model variation availability.

| Description | Optional Feature |
|--|------------------|
| Call Button, Sends call tone to other intercoms on the same audio line | A |
| Primary, controls Talk/Listen function of a Secondary unit | C |
| Secondary, allows hands free operation, default Talk mode | D |
| Foot Pedal Ready, hands free operation of the Talk/Listen switch, pedal sold separately (ADFP) | -2 |
| Auxiliary Signal, remote call button activated contact closure to activate remote strobe for additional attention gathering* | -3 |
| Zoned System Remote, designed to be a remote unit in a zoned system. (Contact factory for zone design assistance) | -6 |
| Noise Canceling Microphone Ready, equipped with a jack for hand held microphone sold separately | -7 |
| Pre-Amp Equipped, pre-amp to power a remote speaker | -8 |
| Remote Volume Control Equipped, equipped with volume control for remote speaker | -M44 |

*LP3 strobe sold separately