

Introducing the new Pathfinder™ Remote Control Head



Pathfinder™ is a compact, programmable siren and light controller now available with a remote surface mount control head. The new remote control head features a four-position progressive slide switch, seven-position rotary switch and nine dual color backlit push-buttons. For convenient visual reference, the Pathfinder emulates the selected pattern of the SignalMaster operation on the front of the control head.

Additional features include easily accessible volume control, bail bracket mount, a channel on the back of the controller for a wire harness, and a USB port on the amplifier for easy programming and customization.

The included noise-canceling microphone uses a RJ11 connector to plug directly into the control head, eliminating the need to run a mic cable back to the amplifier. For increased versatility the amplifier offers a ¼" jack microphone plug option (¼" jack microphone and remote extension kit sold separately).

FEATURES

- 100/200 W siren/light controller with PA and noise canceling microphone
- (4)-position progressive slide switch; seven-position rotary switch and (9) push-buttons
- Built-in dual tone capability
- Built-in Rumbler® Intersection Clearing capability
- Optional FS Vehicle Integration/On-Board Diagnostics Intergration (OBDII)
- Programmable timer feature
- Speaker diagnostic LEDs
- Siren tones, PA, Radio Rebroadcast and Air Horn
- Library of selectable siren tones includes Unitrol and Powercall siren tones
- Horn Ring Transfer and Park Kill
- Backlit LEDs on control faceplate emulate SignalMaster™ directional warning operation
- (7) programmable inputs and (12) programmable solid-state relay outputs
- Convergence Network Configuration Software allows for easy customization of siren and light controls
- (2) Convergence Network ports
- Dual color (Red/Blue) backlit of push-buttons
- Meets or exceeds SAE, California Title 13 and NFPA requirements
- Five-year warranty



Controller Front View



Controller Back View with included RJ11 Microphone



¼" Jack Microphone (sold separately)





SPECIFICATIONS

Specifications	
Input Voltage	12/24 VDC
Standby Current	Less than 0.1 A
Operating Temp	-40°C to +80°C

Specifications			
	Height	Width	Depth
Amplifier	2.5 in (6.4 cm)	6.0 in (15.2 cm)	7.1 in (18.0 cm)
Remote Control Head	2.5 in (6.4 cm)	6.0 in (15.2 cm)	1.4 in (3.5 cm)
Shipping Weight			
3.9 lbs (1.8 kg)			

HOW TO ORDER

Model #	Description	2018 List Price US\$
PF200R	Siren/Light Controller with Remote surface mount controller, 100/200 W, OBDII integration capability, integrated Rumbler® capability, and integrated dual tone capability	\$1,199.00
RUMBLER-3-PF	Siren Amp, Rumbler, secondary warning system, 12 VDC, low frequency tones, hardware kit, housing bands and cradles. Used with PF200 and PF200R to utilize dual tone and Rumbler capabilities	650.00
RBKIT1*	Single Rumbler woofer	299.00
RBKIT2*	Pair of Rumbler woofers	499.00
OBDCABLE6-1	6-ft OBDII interface cable, for use on 2018 Chevrolet Tahoe, 2018 Ford	199.00
OBDCABLE25-1	25-ft OBDII interface cable, for use on 2018 Chevrolet Tahoe, 2018 Ford Police Interceptor Utility, 2018 Ford F-150 and 2018 Ford Interceptor Sedan	199.00
OBDCABLE6-DGCAN	6-ft OBDII interface cable, for use on 2018 Dodge Charger Pursuit and 2018 Dodge Durango	199.00
OBDCABLE25-DGCAN	25-ft OBDII interface cable, for use on 2018 Dodge Charger Pursuit and 2018 Dodge Durango	199.00
MNCT-SD	¼" jack microphone	61.00
RMK	Remote extension kit for ¼" jack microphone	115.00
Z258B577D-03	RJ11 microphone	101.00
Z862302151A	Replacement remote control head	400.00

*Vehicle specific Rumbler brackets sold separately

TIMING

The new remote surface mount controller for the Pathfinder is available to order today.