



Model SLM300 and SLM350 shown with mounting base options (ordered separately)

Models SLM300 and SLM350

StreamLine® Modular Multifunctional Low Profile LED Beacons

Models SLM300 and SLM350 offer a multifunctional LED beacon with high optical performance. Developed with a multiple-input technology, these models offer three separate flash patterns (steady, flashing, and strobe), controllable via wiring selection. The steady light option offers a consistent light source. The flashing mode consists of a single flash, while the strobe effect is a 3x, 5x, or random flash. Two integrated buttons allow the user to select a different light effect per channel and adjust the light output brightness (33%, 66%, 100%) for a truly custom application.

Model SLM300 includes an opaque lens for signaling in close proximities. Model SLM350 includes a fresnel lens for long distance signaling. The body material is a self-extinguishing polycarbonate material with high-impact and UV resistance suitable for outdoor applications.



FEATURES

- Compatible with 12-24 Vac/dc or 120-240 Vac*
- PLC compatible with PNP or NPN connections (Except Dock Base, only NPN)
- Three flash patterns: steady, flashing, and strobe
- Three light intensity levels: 33%, 66%, or 100%
- 100,000-hour LED
- Five LED lamp/lens colors: Amber, Blue, Clear, Green, and Red

- Seven mounting base options
- Type 4X, IP66 enclosure
- IP69K** compliant
- CE and UKCA compliant
- UL and cUL Listed

* Voltage is dependent on selected base (sold separately)

** IP69K with select bases SLMBBS, SLMBD, SLMBP, and included SLM-RR accessory

MODEL	VOLTAGE	LENS	FLASH RATE/MINUTE (FLASH MODE)	FLASH RATE/MINUTE (STROBE MODE)
SLM300*	12-24 Vac/dc or 120-240 Vac	Opaque	120 (+/-10)	85(+/-10)
SLM350*	12-24 Vac/dc or 120-240 Vac	Fresnel	120 (+/-10)	85 (+/-10)

* Indicates color: (A) Amber, (B) Blue, (C) Clear, (G) Green, or (R) Red

MAXIMUM OPERATING CURRENT (mA)

12 Vdc	24 Vdc	12 Vac	24 Vac	120 Vac	240 Vac
250	155	250	155	100	75


Weight (unit(s) + base = total weight)

SLM200	VOLTAGE	SHALLOW BASE	DEEP BASE	WALL MOUNT	PIPE MOUNT	TWIN WALL MOUNT	2-STACK DOCK BASE	3-STACK DOCK BASE
3.88 oz	12-24 Vac/dc	2.12 oz 0.06 kg	4.23 oz 0.12 kg	6.70 oz 0.19 kg	5.29 oz 0.15 kg	9.17 oz 0.26 kg	14.46 oz 0.41 kg	21.16 oz 0.60 kg
0.11 kg	120-240 Vac	—	6.0 oz 0.17 kg	8.47 oz 0.24 kg	6.70 oz 0.19 kg	12.35 oz 0.35 kg	16.58 oz 0.47 kg	24.69 oz 0.70 kg

StreamLine® Modular Multifunctional Low Profile LED Beacons (SLM300 and SLM350)

SPECIFICATIONS

Lamp Life: 100,000 Hours
 Light Source: LED
 Operating Temperature Range: -40° to 131°F (-40° to 55°C)



ACCESSORIES

Accessories for Dock Base



Mounting Base Options

Mounting bases are rated Type 4X. Final product rating is determined by top module. In combination with SLM300 or SLM350 the unit is Type 4X, IP66. For IP69K compliance, pair with shallow, deep, or pipe-mount base and included retaining ring (SLM-RR).

HOW TO ORDER

- Specify model number SLM300 and color for Opaque Lens or SLM350 and color for Fresnel Lens
- Specify required mounting base (see chart)
- Optional dome guard:
For shallow mounting base (SLMDG0)
For deep mounting base (SLMDG1)
- Accessories for Twin and Wall Mount Bases:
Cable Gland, M20, Gray, 2 Pack (K77700416)
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base:
1-inch NPT Adapter (SLMNPT1)
1/2-inch NPT Adapter (SLMNPT2)
- Accessories for Dock Base:
Wall Mount Bracket (SLMB23W)
1/2-inch NPT Adaptor (SLMB23N)
Retaining Ring (SLM-RR)
Light Visor (SLMB23V)

 Shallow Base	Model Number	Base Color	Voltage	
	SLMBS-012-024GY	Gray	12-24 Vac/dc	
 Deep Base	SLMBD-012-024GY	Gray	12-24 Vac/dc	
	SLMBD-012-024R	Red	12-24 Vac/dc	
	SLMBD-120-240GY	Gray	120-240 Vac	
	SLMBD-120-240R	Red	120-240 Vac	
 Wall Mount	SLMBW-012-024GY	Gray	12-24 Vac/dc	
	SLMBW-120-240GY	Gray	120-240 Vac	
 Pipe Mount	SLMBP-012-024GY*	Gray	12-24 Vac/dc	
	SLMBP-120-240GY*	Gray	120-240 Vac	
 Twin Wall Mount	SLMBT-012-024GY	Gray	12-24 Vac/dc	
	SLMBT-120-240GY	Gray	120-240 Vac	
 2-Stack Dock Base  3-Stack Dock Base	SLMB2-024GY*	Gray	24 Vac/dc	
	SLMB2-120-240GY*	Gray	120-240 Vac	
	SLMB3-024GY*	Gray	24 Vac/dc	
	SLMB3-120-240GY*	Gray	120-240 Vac	
NOTE: Dock bases allow one function per position and include visors. Dock bases are NPN compatible only.				

* Installation of included retaining ring is required for pipe and dock bases.

Rev. B