



► Atkinson Dynamics | Intercoms

FEATURES

- Integrated filtering to reduce outside noise and interference.
- Multi-volt; units operate at both 12 and 24-volts.
- Reliable two or three-way communication in any conditions.
- Variety of options available to satisfy communications needs.
- Simple to use and easy to install.
- Designed and built to protect against the elements and withstand rough conditions.

Atkinson Dynamics intercoms provide reliable communication with superior sound quality. Each basic intercom is fully equipped to receive, amplify, and send signals.

A volume control on the face of each unit allows the user to adjust the output level to overcome noisy environments. A talk/listen switch activates the built-in microphone and defaults to the listen position when released.

The rugged exterior of Atkinson Dynamics intercoms provides protection against the elements in any environment. The corrosion-resistant cast aluminum housing is carefully sealed to keep the interior free of moisture and dust.

Atkinson intercoms can be installed as two or three-way communication systems. (See back for examples.) Various systems are available including the standard "master" and "hands-free" system, a remote speaker two-way system, and other systems utilizing various options including headset and microphone jacks.

Every Atkinson intercom is multi-volt and can work on either 12 or 24-volt systems without any additional parts or labor for installation. Also, each Atkinson intercom is designed with internal noise filters and circuitry to produce a clear, quality sound for premium performance.



ADSS-25-Z



ADSF-25-Z

Some two-way Atkinson systems utilize a smaller, hands-free remote speaker to save space.

Intercoms

Model	Description
AD26-Z	Push to talk, 12/24V
AD26-8-M44-Z	Push to talk, pre-amplifier, remote volume, 12/24V, use with ADSS-25 or ADSF-25
AD26C-Z	Master intercom, push to talk, 12/24V, use with hands-free intercom
AD26C-1-Z	12/24VDC, master intercom, power audio in single cable
AD26D-1-Z	12/24VDC, auxillary intercom, use with AD26C-1-Z

Speakers


Model	Description	Operating Temperate	Ship Weight
ADSF-25-Z	25W, flush mount	350.00	9 lbs. (4.1 kg)
ADSS-25-Z	25W, swivel mount	350.00	6 lbs. (2.7 kg)

Accessories


Model	Feature	Description
ADNCM	Microphone	Noise-canceling hand-held microphone; use with intercoms w/-7 option

Basic Systems



AD26C-Z




AD26D-Z




AD26-8-M44-Z ADSS-25-Z



AD26C-Z



AD26C-Z



AD26D-Z

