



▶ Commander® LC | Area Lighting

FEATURES

- Generates up to 20,000 lumens of white light; Recess mount generates 15,000 lumens
- Available in 12/24 VDC models
- Advanced lens design focuses 100% of the LED light directly where it is needed most
- Cost effective LED lamphead
- Unique LED design provides more light in a compact light head (COMLC11K)
- Instant-on at full intensity
- Five-year warranty on LED components

APPROVALS

- IP68

Cost-effective Area Light

Commander® LC is a cost-effective LED area light solution. Uniform high-quality white LED lights and an advanced lens design directs powerful light output onto the emergency scene. Full brightness is instant once power is applied. These light heads are available as portable and surface or recess mounts.

Recess Mount

Commander LC recess mounts have a slim profile designed to complement the side of the vehicle's cab. These models provide an impressive 15,000 lumens of light and are available in 12/24 VDC.

Portable Commander LC

Commander LC portable models come equipped with a sure-grip modeled handle. This easy to grip handle stays cool when the light head is illuminated allowing for the light source to be moved to a specific location. Ideal for upgrading are the optional mounting feet for telescopic poles and tripods.



Commander LC lens focuses more LED light on the scene and objects in the distance.



Light heads

- COMLC11K Commander LC, 11K lumens, 12/24 VDC flood LED light head
- COMLC20K Commander LC, 20K lumens, 12/24 VDC flood LED light head

Light heads with Poles

- COMLC11K-530-H Commander LC, 11K lumens, 12/24 VDC, side mount bottom-raise pole, 3.5" offset brackets
- COMLC11K-540-TW Commander LC, 11K lumens, 12/24 VDC, side mount top-raise pole, 3.5" offset brackets, top wire exit
- COMLC20K-530SW-H Commander LC, 20K lumens, 12/24 VDC, side mount bottom-raise pole, 3.5" offset brackets, raised pole indicator
- COMLC20K-540TW-H Commander LC, 20K lumens, 12/24 VDC, side mount top-raise pole, 3.5" offset brackets, top wire exit

Fixed Mount/Recessed Mount/Brow Mount

- COMLC11K-570-ON Commander LC, 11K lumens, 12/24 VDC, fixed top mount, on/off switch
- COMLC11K-850 Commander LC, 11K lumens, 12/24 VDC, flat mount
- COMLC15K-210 Commander LC, 15K lumens, 12/24 VDC, recessed mount
- COMLC20K-570 Commander LC, 20K lumens, 12/24 VDC, fixed top mount
- COMLC20K-800* Commander LC, 20K lumens, 12/24 VDC, contour brow mount

*specify vehicle chassis when ordering

Contact the factory for additional model configurations.

Physical Dimensions			
	Height	Width	Depth
COMLC11K	9 in	7 5/8 in	5 3/16 in
COMLC20K	9 in	11 1/2 in	5 3/16 in
COMLC15k-210	5 7/8 in	13 7/8 in	2 in

Pole Dimensions	
530 POLE (side mount bottom-raise)	
Overall Height	58 in. (without light head)
Inner Pole Extension	20 in.
540 POLE (side mount top-raise)	
Overall Height	58 in. (without light head)
Inner Pole Extension	39 in.

Technical Specifications			
	Volts	Current Draw	Lumens
COMLC11K	12/24 VDC	7.5/3.75 A	11,000
COMLC20K	12/24 VDC	13.0/6.5 A	20,000
COMLC15K-210	12/24 VDC	11.0/5.5 A	15,000



Commander is trademark of Federal Signal Corporation.

©2019 Federal Signal Corporation. M8032 I 719

