

Firebolt® Class 3 LED

Beacon



FEATURES

- Single flash pattern
- (3) high-powered LEDs
- Cost effective
- Permanent and magnet mount models available
- Polycarbonate base and dome
- Multi-voltage, 12/24 Vdc
- Three-year warranty

A superior warning signal

Firebolt® Class 3 LED beacon produces a superior warning signal to promote work zone safety. The LED technology in the Firebolt LED allows for a minimal Amp draw of less than 0.5 Amp while meeting Class 3 standards.

Built for versatility and durability

Designed to meet the demands of a variety of work zones including snow plows, forklifts, utility trucks and construction vehicles; the Firebolt Class 3 LED is made of a shatterproof, polycarbonate dome and base that includes an o-ring to help protect against moisture. Firebolt Class 3 LED is available in both permanent and magnet mount.

APPROVAL

- SAE J845, Class 3



Permanent mount



Magnet mount with accessory plug

HOW TO ORDER

LED Color **A** Dome Color **A**

220350-02	Permanent mount, Amber LEDs, Amber dome
220360-02	Magnet mount, accessory plug, Amber LEDs, Amber dome

SPECIFICATIONS

	PERMANENT MOUNT	MAGNET MOUNT
OPERATING VOLTAGE	12/24 Vdc	
CURRENT DRAW	< 0.5A @ 12 Vdc <0.25A @ 24 Vdc	
OPERATING TEMP	-22° to +149° F [-30° to +65° C]	
PHYSICAL SPECIFICATIONS		
DIAMETER	5.1 in (12.9 cm)	
HEIGHT	3.8 in (9.6 cm)	
SHIP WEIGHT	0.9 lb (0.4 kg)	1.5 lb (0.7 kg)

