



Federal Signal releases three new cameras to our Mobile Camera Line.



	CAMCCD-COMREAR	CAMCCD-REARMIR	CAMCCD-REARMIR-NIR
Camera Specifications			
Voltage	12 VDC	12 VDC	12 VDC
Power Consumption	<2.0 W	< 2.5 W	< 2.5 W
Low-light/Night Vision	8 Infrared LEDs with photo sensor	15 Infrared LEDs with photo sensor	N/A
Microphone	Integrated	Integrated	Integrated
Environmental Rating	IP68 (water proof and dust-resistant)	IP68 (water proof and dust-resistant)	IP68 (water proof and dust-resistant)
Operating Temp. Range	30°F to 158°F (-22°C to 70°C)	-22°F to 158°F (-30°C to 70°C)	-22°F to 158°F (-30°C to 70°C)
Physical Specifications			
Dimensions	1.3 in x 1.3 in x 1.6 in (3.4 cm x 3.4 cm x 4.0 cm)	3.43 in x 2.76 in x 2.34 in (8.7 cm x 7.0 cm x 6.0 cm)	3.43 in x 2.76 in x 2.34 in (8.7 cm x 7.0 cm x 6.0 cm)
Weight	1.43 lb (0.65 kg)	0.76 lbs (0.34 kg)	0.76 lbs (0.34 kg)

HOW TO ORDER

Model #	Description	2016 List Price US\$
CAMCCD-COMREAR	Compact mirroring rear view camera with night vision and audio	\$145.00
CAMCCD-REARMIR	Mirroring rear view camera with night vision and audio	\$155.00
CAMCCD-REARMIR-NIR	Mirroring rear view camera with audio, No Infrared LEDs	\$155.00

For more information, contact your local Federal Signal sales representative, Amber Customer Support at 800-824-0254 or visit our website at www.fedsig.com.