



MicroPulse® Steady Burn models are available for use with Pathfinder™ Sirens

Popular MicroPulse® models are now available as steady burn models for use with the Pathfinder™ Siren. The combination of MicroPulse Steady Burn models and the Pathfinder Siren allow the Pathfinder to control lights around the vehicle by utilizing flash patterns in the siren, syncing/alternating light heads, and dimming light heads.



FEATURES

Overall:

- Intended to be flashed with the Pathfinder siren or other external flasher
- Dimming capability
- All steady burn models are dual color
- Wiring:

Ground - Black wire

+VDC for color 1 - (2) Red wires*

+VDC for color 2 - White wire

- Sync/alternate with other MicroPulse Steady Burn models
- No built-in flash patterns, utilizes the flash patterns of the Pathfinder siren (sold separately)
- 3-year warranty

MicroPulse Ultra Steady Burn models

- Utilizes (12) or (24) high-powered LEDs
- Ultra low-profile design offers a wide range of mounting options
- Ultra 6 Steady Burn H=1.3 in, L=5.2 in, D=0.4in Ultra 12 Steady Burn H=1.9 in, L=5.3in, D=0.45in

MicroPulse Wide Angle Steady Burn models

- Utilizes (12) LEDs, 180-degree light spread
- Perfect for mounting on push bumpers, rub rails, side mirrors, and spoilers
- Wide Angle 9 Steady Burn H=1.5 in, L=5.1 in, D=1.5in

^{*}Must connect 2 Red positive wires for product to function properly

MARKETING UPDATE





HOW TO ORDER

Model #	Description	2019 List Price US\$	
MicroPulse® Ultra, Steady Burn, Dual Color, Surface Mount, 12/24 VDC			
MPS620UX-BW	12-LED light head, Blue/White, Clear lens	\$166.00	
MPS620UX-RW	12-LED light head, Red/White, Clear lens	166.00	
MPS620UX-BA	12-LED light head, Blue/Amber, Clear lens	166.00	
MPS620UX-BR	12-LED light head, Blue/Red, Clear lens	166.00	
MPS1220UX-BW	24-LED light head, Blue/White, Clear lens	197.00	
MPS1220UX-RW	24-LED light head, Red/White, Clear lens	197.00	
MicroPulse Wide Angle, Steady Burn, Dual Color, Surface Mount, 12/24 VDC			
MPSW9X-BW	12-LED light head, Blue/White	229.00	
MPSW9X-RW	12-LED light head, Red/White	229.00	

WIRING

To +VDC for Color1 (fuse rating @ 2A): (Connect to external flasher for warning purpose.)	RED x 2	
To +VDC for Color2 (fuse rating @ 2A): (Connect to external flasher for warning purpose.)	WHITE	\neg
To Vehicle Chassis Ground:	BLACK	-
INSTALLATION: Surface mount		

TIMING

MicroPulse® Steady Burn models are available to order today.

For more information, please contact your local Federal Signal sales representative or visit our website at www.fedsig.com.