

# PA4000

## Electronic Siren



### FEATURES

- 200 W, remote amplifier siren system
- Diagnostic feature provides system status
- WAIL, YELP, PRIORITY tones
- Noise canceling microphone included
- Remote Control Head is designed to mount flush on any flat surface
- Backlit instrument panel for nighttime viewing
- Easy to install and service
- Three-year warranty

### APPROVALS

- Meets Class A requirements for sound output with any pair of Federal Signal 100-watt speakers.

#### Several Great Features, One Low Price

The PA4000 is a full-featured siren amplifier system with a remote control head that can be flush mounted to any flat surface. The design of the PA4000 siren system is ideal for use in ambulances, police cars, fire apparatus and command vehicles.

#### Meets Industry Specifications

Continuing the Federal Signal unmatched tradition of quality, the PA4000 incorporates the latest technology for superior reliability. This 200 W siren is engineered to meet Class A specifications and can drive two high-powered 100 W speakers. Designed for easy installation, the PA4000 consists of an amplifier unit, flush mount control head, and RJ-45 wire to connect the two components.

#### Diagnostic Feature

The PA4000 has a unique diagnostic feature that checks for abnormal operation of the speaker system. Two LEDs light up to indicate speaker operation during test mode. The siren emits an intermittent low-level sound picked up through the speakers and causes the LEDs to flash when the sound is successfully transmitted.

The PA4000 includes an AUX/IN feature that will place the siren in Wail mode when Manual. The AUX/OUT feature drives an external relay that may be used to control warning lights. The AIR HORN/SIREN feature is activated using a paddle switch on the control panel. Also included is HORN RING, controlled by a slide-switch and TAP II, enabling the driver to change the active siren tone via the vehicle's horn ring.

## HOW TO ORDER

**PA4000** 200 W electronic siren with remote amplifier and flush mount control

## SPECIFICATIONS

<b>AUDIO OUTPUT POWER</b>	200 W
<b>INPUT VOLTAGE</b>	11/16 Vdc
<b>NOMINAL OUTPUT VOLTAGE</b>	62 V peak-to-peak
<b>STANDBY CURRENT</b>	250 mA
<b>INPUT CURRENT, OPERATING</b>	13 A
<b>OPERATING TEMP.</b>	-22° to +149° F (-30° to + 65° C)
<b>POLARITY</b>	Negative ground only
<b>FREQUENCY RANGE</b>	725 to 1600 Hz

### PHYSICAL SPECIFICATIONS

	CONTROL HEAD	AMPLIFIER
<b>LENGTH</b>	6.3 in (16.0 cm)	6.9 in (17.5 cm)
<b>WIDTH</b>	2.9 in (7.4 cm)	2.9 in (7.4 cm)
<b>HEIGHT</b>	1.5 in (3.8 cm)	4.8 in (12.2 cm)

### SHIP WEIGHT

7.0 lb (3.2 kg)



Warning: Sirens and Speakers may produce LOUD sounds necessary to request the right-of-way. Sirens and Speakers may cause hearing damage. Wear hearing protection.