

Littlite®

Accessories



FEATURES

- Flexible, "goose-neck" task lights that can be easily aimed precisely where you need it
- LED or halogen models
- Available with On/Off switch or rheostat "dimmer" control
- 12" and 18" lengths
- Includes a 24" wire length for installation
- Five-year warranty

Littlite® sleek, low-profile gooseneck lamps efficiently produce light in a concentrated area and can easily be aimed exactly where you need it. Made of sturdy metal and finished in durable black, baked enamel, all Littlite lamps and accessories are designed to meet the most demanding needs. The stylish hood dissipates heat and extends surface life. The units are equipped with a permanently attached gooseneck that extends from either the end or top of the chassis and are controlled by your choice of a rheostat or an on/off switch.

LED Littlite lamps for console lighting are composed of Red and White LEDs, eliminating the need for a red filter. A Blue and UV LED options are also available. The UV LED model includes a UV light mode perfect for checking security watermarks on currency, driver licenses, passports, and anything else that utilizes UV security marks. Amperage draw has also been reduced to only 100 mA, providing a cooler, longer-lasting operation.

Halogen Littlite lamps emit a crisp, bright White light in a tightly controlled pattern for use in any task involving accurate, close or detailed work. A colored Red filter easily slides into place over the lamp for night use within any police, fire, ambulance, emergency or utility vehicle.

Littlite gooseneck lamps include 24-inches of automotive wiring for easy installation in any 12-volt system.



HOW TO ORDER

LED MODELS

NECK EXTENDS FROM TOP OF CHASSIS, HORIZONTAL MOUNT

- LF12TSB-LED 12", On/Off switch control, wired base, White/Red light modes
- LF12TS-LED 12", On/Off switch control, White/Red light modes
- LF18TSB-LED 18", On/Off switch control, wired base, White/Red light modes
- LF18TSB-LED-BLUE 18", On/Off switch control, wired base, White/Blue light modes
- LF18TS-LED 18", On/Off switch control, White/Red light modes

NECK EXTENDS FROM END OF CHASSIS, VERTICAL MOUNT

- LF12ES-LED 12", On/Off switch control, White/Red light modes
- LF12ESB-LED 12", On/Off switch control, wired base, White/Red light modes
- LF18ES-LED 18", On/Off switch control, White/Red light modes
- LF18ER-LED-UV 18", Rheostat control, UV/White/Red light modes

HALOGEN MODELS

HALOGEN MODELS INCLUDE RED FILTER THAT SLIDES INTO PLACE OVER THE LAMP FOR NIGHT VISION USE

NECK EXTENDS FROM END OF CHASSIS, VERTICAL MOUNT

- LF12ERB 12", Rheostat control, wired base
- LF12ESB 12", On/Off switch control, wired base
- LF18ERB 18", Rheostat control, wired base

NECK EXTENDS FROM TOP OF CHASSIS, HORIZONTAL MOUNT

- LF12TRB 12", Rheostat control, wired base

SPECIFICATIONS

OPERATING VOLTAGE	12.8 Vdc
HALOGEN LAMP TYPE	Bi-pin halogen, 5 W
CURRENT DRAW	0.5 A nominal (halogen) 0.1 A nominal (LED)
OPERATING TEMP.	32° to +185° F [0° to +40° C]
STORAGE TEMP.	-4° to +185° F [-20° to +85° C]

PHYSICAL SPECIFICATIONS

	BASE	LAMPHEAD	GOOSENECK
LENGTH	1.0 in (2.54 cm)	0.6 in (1.5 cm)	12 in (30.5 cm) or 18 in (45.7 cm)
WIDTH	3.0 in (7.62 cm)	2.5 in (6.35 cm)	--
HEIGHT	0.7 in (1.78 cm)	0.5 in (1.27 cm)	--
SHIP WEIGHT	1.0 lb (0.5 kg)		



LF18ER-LED-UV Includes a UV light mode perfect for checking security watermarks on currency, driver licenses, passports, and anything else that utilizes UV security marks.



Littlite is a trademark of CAE, Inc.