

8200S SignalMaster™ Arrow

Directional Warning



FEATURES

- Arrow style lights available in 16- and 10-head LED versions
- 18-inch whip with water-tight connector standard on all units
- Selectable 15- and 30-ft extensions cables required
- (14) selectable flash patterns
- Optional 8-button controller available
- Aluminum housing with rail design compatible with (7) mounting brackets
- 12 Vdc
- Three-year warranty

Performance to Keep You Safe

The 8200S SignalMaster Arrow is a high-intensity warning system designed to direct traffic approaching from the rear of a stationary vehicle. Equipped with (10) or (16) LED lights heads, the 8200S SignalMaster Arrow delivers an impressive optical performance suitable for several vehicle applications.

Versatility For the Job

The full feature 8200S SignalMaster Arrow comes programmed with (14) eye-catching flash patterns along with left, right, center-out directional warning and is available in Amber LEDs. In addition, the rail design allows users to mount with (7) SignalMaster brackets.

APPROVALS

- SAE J595
- CCR Title 13



HOW TO ORDER

LED Color A Lens Color C

STEP 1:

Choose one of the popular models below or contact a local Federal Signal representative or distributor

8200SMA16-A	16-head, Amber, 51-inch (4-head arrows, 8-head stick)
8200SMA10-A	10-head, Amber, 31-inch (2-head arrows, 6-head stick)
8200SMA10-A-2	10-head split, Amber, (2) 2-head arrows, 3-head stick

STEP 2:

Choose a discrete extension cable (15-ft or 30-ft) or serial 8-button controller for operation
 [Must order (1) with each 8200S SignalMaster]

SMCABLE-15	15-ft SignalMaster cable, discrete
SMCABLE-30	30-ft SignalMaster cable, discrete
SMCONTROL	SignalMaster serial controller, cable length 20-ft

ACCESSORIES

SW200-B	4-switch box with bail bracket, for use with SMCABLE
SW300-B	6-switch box with bail bracket, for use with SMCABLE
SW400SS-B	4-switch with slide switch box and bail bracket, for use with SMCABLE
SMEXTENSION-15	15-ft extension cable, for use with SMCONTROL
SMEXTENSION-30	30-ft extension cable, for use with SMCONTROL



SMCONTROL
8-button controller

SPECIFICATIONS

	16-HEAD ARROW	10-HEAD ARROW	10-HEAD ARROW SPLIT
OPERATING VOLTAGE		12 Vdc	
CURRENT DRAW		0.5 A per head	
OPERATING TEMP		-40° to +176° F (-40° to +80° C)	
FLASH PATTERNS		14	
LED COLOR		Amber	
LENS COLOR		Clear	
PHYSICAL SPECIFICATIONS			
LENGTH	53.05 in (135.0 cm)	33.06 in (84.0 cm)	16.56 in (42.0 cm) per side
WIDTH	2.11 in (5.4 cm)	2.27 in (5.8 cm)	2.27 in (5.8 cm)
HEIGHT	20.20 in (51.3 cm)	11.90 in (30.2 cm)	11.90 in (30.2 cm)
SHIP WEIGHT	18 lb (8.2 kg)	13.5 lb (6.1 kg)	13.5 lb (6.1 kg)

MOUNTING STYLE

*Mounting brackets sold separately

Rail design compatible with seven Federal Signal SignalMaster™ mounting brackets.



320310



320320



320330



320340



320350



SLB-001



SLB-0012



SignalMaster is a trademark of Federal Signal Corporation.