



► Model LP57

StreamLine® Mini LED Beacon Series

Model LP57 is available as a single color or multicolor LED light that is ideal for applications requiring low profile signaling. Single color models are steady burn and available in five colors. Multicolor models feature a single flash pattern and offer seven color options in one device.

All LP57 models have a clear, opaque lens for signaling in close proximities. The LP57 enclosure is rated Type 4X and offers a self-extinguishing polycarbonate housing that protects against vibrations, dust, and atmospheric elements. Each model features either a M12 Cable Gland with 12" (300mm) leads or M12 4-Pin Quick Connect.


FEATURES

- Available in 24VDC
- Choice of M12 Cable Gland or M12 Quick Connect
- 100,000 hour LED
- Single color models are steady burn and available in five colors (Amber, Blue, Green, Red, and White)
- Multicolor models feature a single flash pattern and offer seven color options in one device (Amber, Blue, Cyan, Green, Magenta, Red, and White)
- Self-extinguishing polycarbonate housing
- Type 4X, IP66 enclosure
- IP69K compliant
- CE and UKCA compliant
- UL and cUL Listed

| | VOLTAGE | LENS | FLASH RATE/MINUTE (1X FLASH) | MAXIMUM OPERATING CURRENT (mA) |
|------------------------|---------|--------|---------------------------------|-----------------------------------|
| LP57-024* | 24VDC | Opaque | NA | 40 |
| LP57-024*-Q | 24VDC | Opaque | NA | 40 |
| LP57-024RGB-F | 24VDC | Opaque | 120 (+/- 10) | 80 |
| LP57-024RGB-F-Q | 24VDC | Opaque | 120 (+/- 10) | 80 |

* Indicates color: (A) Amber, (B) Blue, (C) Clear, (G) Green or (R) Red

StreamLine® Mini LED Beacon Series (LP57)




SPECIFICATIONS

| | |
|------------------------------|-----------------------------------|
| Lamp Life: | 100,000 Hours |
| Light Source: | LED |
| Operating Temperature Range: | -22°F to 122°F -30°C to 50°C |

| | M12 Cable Gland | M12 Quick Connect |
|------------------------|--------------------|--------------------|
| Height | 2.20" (56mm) | 2.20" (56mm) |
| Height (above surface) | 2.95" (56mm) | 2.87" (73mm) |
| Length | 2.76" (70mm) | 2.76" (70mm) |
| Net Weight | 0.19 lbs (0.08 kg) | 0.31 lbs (0.14 kg) |
| Shipping Weight | 0.50 lbs (0.23 kg) | 0.50 lbs (0.23 kg) |

HOW TO ORDER

Single Color Steady Burn Models



Multicolor Flash Models RGB-F Multicolor Flash