

# StreamLine<sup>®</sup>

MODULAR SERIES

One concept. Endless solutions.



A New and Unique Modular  
Concept in Signaling Devices



# StreamLine®

MODULAR SERIES

When you have a range of products that can be mixed and matched with each other offering a multitude of solutions. . . When you have a range of devices that can perform multiple functions. . . When you have devices that allow you to control more than one channel independently. . . When you have a range of bases that allow you to mount your devices in various manners. . . When you have all this, you have Federal Signal's new line of StreamLine® Modular products. . . The first range of devices engineered to be Modular, Multifunctional, Multiple Input and Multivoltage. At Federal Signal we do not take challenges that are easily solvable. . . we do not take the ordinary for granted. . . and we make sure our daily mission is to deliver the best possible Total Solution to our customers. Welcome to a new opportunity of signaling options.



A range of multifunctional signals based on an innovative multiple input technology allowing each function of the device to be controlled via independent electrical contacts, creating different levels of alarm with one single device.



Seven different base shapes in voltages 24VAC/DC, 12-24VAC/DC, and 120-240VAC; a perfect fit for any application.

## Signals & Bases



Signals and bases can be matched together with a simple snap-on technology allowing an easy and safe installation procedure, even in the most challenging environments.

# StreamLine® MODULAR SERIES

The Federal Signal StreamLine® Modular Series is a new and unique concept developed to deliver a customized product tailored to each specific application.



High Output  
LED Combination  
Audible/Visual Signal  
Model SLM600

A B C G R

LED Beacon with  
Steady/Flashing/Rotating  
Options  
Model SLM100

A B C G R



LED Beacon with  
Flashing/Simulated  
Strobe/Random  
Options  
Model SLM200

A B C G R



LED Co  
Audible  
Mod

A B



Twin  
12-24 VAC  
120-240 V



Deep  
12-24 VAC/DC  
120-240 VAC



Wall  
12-24 VAC/DC  
120-240 VAC



Pipe  
12-24 VAC/DC  
120-240 VAC



Low Profile LED  
with Steady/Fla  
Strobe Options  
Model SLM

A B C G



Combination  
Electronic/Visual Signal  
Model SLM500

C G R

VAC/DC  
VAC

ses

Shallow  
12-24 VAC/DC

LED Beacon  
Flashing/Simulated  
Model SLM1300/SLM350

R

High Output  
Electronic Sounder  
Model SLM800

2-stack  
Dock Base\*  
24 VAC/DC  
120-240 VAC

3-stack  
Dock Base\*  
24 VAC/DC  
120-240 VAC

Low Profile  
Multicolor/Multipattern  
LED Beacon  
Model SLM1400/SLM1450\*\*

A B C CY G M R Y

\* Not compatible with models SLM600 and SLM800

\*\* SLM1400/SLM1450 are compatible with all bases. SLM1400-ARROW is compatible with the shallow base, deep base, wall mount, pipe mount, and twin wall mount. SLM1400-ARROW-DL is compatible with the 2-stack and 3-stack dock base

# Signals



A B C G R

## LED Beacon with Steady/Flashing/Rotating Options SLM100

Multifunctional LED beacon with high optical performance. SLM100 allows three separate light effects (steady, flashing or rotating) controllable via independent electric contacts.



A B C G R

## LED Combination Audible/Visual Signal SLM500

Multifunctional LED beacon and sounder allows three separate levels of alarm (alert, pre-alarm, alarm) controllable via independent electric contacts. SLM500 offers two light effects (steady or flashing) and 64 different tones (selectable via dip-switch) through two inputs, adjustable between 65 dB(A) and 105 dB(A).



A B C G R

## LED Beacon with Flashing/Simulated Strobe/Random Options SLM200

Multifunctional LED beacon with high optical performance. SLM200 allows three separate light effects (flashing, simulated strobe or random) controllable via independent electric contacts.



A B C G R

## High Output LED Combination Audible/Visual Signal SLM600

Multifunctional LED beacon and sounder allows three separate levels of alarm controllable via independent electric contacts. SLM600 offers two light effects (steady or flashing) and 64 different tones (selectable via dip switch) through two inputs, adjustable between 65 dB(A) and 115dB(A).



A B C G R

## Low Profile LED Beacon with Steady/Flashing/Strobe Options SLM300 and SLM350

Multifunctional LED beacon engineered to satisfy the most demanding applications. SLM300/SLM350 allows three different light effects (steady, flashing, strobe) controllable via independent electric contacts making this device the perfect choice for most applications. Available with Proximity and Directional lenses, SLM300/SLM350 is ideal where gaining attention is a must.



A B C CY G M R Y

## Low Profile Multicolor/Multipattern LED Beacon SLM1400 and SLM1450

Multicolor, multipattern LED beacon allows for three levels of alarm. For each channel, eight different colors (amber, blue, clear, cyan, green, magenta, red and yellow) and five light effects (steady, 1x flash, 2x flash, 5x flash and random) can be selected. SLM1400 and SLM1450 are offered with opaque and fresnel lens types. SLM1400-ARROW and SLM1400-ARROW-DL feature a directional arrow with an opaque lens

# Signals



## Electronic Sounder SLM700

Multifunctional electronic sounder allows two separate levels of alarm (pre-alarm, alarm) controllable via independent electric contacts. SLM700 offers 64 different tones through two separate inputs, adjustable between 65 dB(A) and 105 dB(A).



## High Output Electronic Sounder SLM800

Multifunctional electronic sounder allows two separate levels of alarm controllable via independent electric contacts. SLM800 offers 64 different tones through two separate inputs, adjustable between 65dB(A) and 115dB(A).

# Bases



**SHALLOW** Base designed for flat surface mounting where cabling occurs from the bottom of the device and where a compact designed is required.



**TWIN** Base is designed for lateral/wall mounting. This multifunctional mount accommodates two Stream-Line® modules creating unique combinations between visual and acoustic devices.



**DEEP** Base designed for flat surface mounting. This base includes two M20 cord grips making this solution ideal for mounting these units in a series.



**2-STACK DOCK\*** Base is designed for lateral or wall mounting, and accommodates two StreamLine® audible or visual top modules. Dock base comes standard with a visor. If additional side visibility is required, the visor can be interchanged with SLM-RR retaining ring (sold separately).



**WALL** Base designed for lateral/wall mounting. This unit includes two M20 cord grips making this product suitable also when it's not possible to wire the base of the signaling device.



**3-STACK DOCK\*** Base is designed for lateral or wall mounting, and can accommodate three StreamLine® audible or visual top modules. Dock base comes standard with a visor. If additional side visibility is required, the visor can be interchanged with SLM-RR retaining ring (sold separately).



**PIPE** Base designed for pipe mounting installations. This base allows for any Stream-Line® unit to be installed on a 1-1/2" NPT threaded pole. Every pipe mount unit also comes standard with a 1/2" NPT adapter.

\* Not compatible with models SLM600 and SLM800

SLM1400/SLM1450 are compatible with all bases. SLM1400-ARROW is compatible with the shallow base, deep base, wall mount, pipe mount, and twin wall mount. SLM1400-ARROW-DL is compatible with the 2-stack and 3-stack dock base

STREAMLINE® MODULAR

# Stainless Steel Dome Guards

Available in 5 sizes  
as an optional  
accessory.



**FEDERAL SIGNAL**  
Safety and Security Systems

2645 Federal Signal Drive, University Park, IL 60484

Phone: 708.534.4756 Fax: 708.534.4852

[www.fedsig.com](http://www.fedsig.com)

© 2023 Federal Signal Corporation Printed in USA S220 | 0323