



Model SLM700 shown with mounting base options  
(ordered separately)

► Model SLM700

## StreamLine® Modular Electronic Sounder

Model SLM700 is a multifunctional electronic sounder developed with a multiple input technology that produces two different tones (one per channel), controllable via independent electric contacts.

There are 64 unique tones to select from across two switches (32 tones per switch). The volume of the tone is adjustable between 86-105 dBa @ 1m at three output levels (high, medium, low) through an integrated button. Model SLM700 body material is a self-extinguishing polycarbonate material with high impact and UV resistance suitable for outdoor applications.

### FEATURES

- Compatible with 12-24VAC/DC or 120-240VAC\*
- PLC compatible with PNP or NPN connections (Except Dock Base, only NPN)
- Choice of 64 selectable tones (32 per input selectable via DIP switch)
- Produces two tones at three adjustable tone levels
- Adjustable volume between 76 dBa to 95 dBa @10' (86-105 dBa @ 1m)
- Seven mounting base options
- Type 3R, IP65 enclosure
- CE and UKCA compliant
- UL and cUL Listed

\*Voltage is dependent on selected base (sold separately).

| MODEL           | VOLTAGE                      | DECIBELS<br>MIN.-MAX. |        | MAXIMUM OPERATING CURRENT (mA) |       |       |       |        |        |
|-----------------|------------------------------|-----------------------|--------|--------------------------------|-------|-------|-------|--------|--------|
|                 |                              | 10'                   | 1M     | 12VDC                          | 24VDC | 12VAC | 24VAC | 120VAC | 240VAC |
| <b>SLM700 *</b> | 12-24VAC/DC or<br>120-240VAC | 76-95                 | 86-105 | 85                             | 60    | 280   | 190   | 125    | 90     |

\*For body color, indicate GY for Gray or R for Red.


### Weight (unit(s) + base = total weight)

| SLM700             | VOLTAGE     | SHALLOW<br>BASE    | DEEP<br>BASE       | WALL<br>MOUNT      | PIPE<br>MOUNT      | TWIN<br>WALL<br>MOUNT | 2-STACK<br>DOCK<br>BASE | 3-STACK<br>DOCK<br>BASE |
|--------------------|-------------|--------------------|--------------------|--------------------|--------------------|-----------------------|-------------------------|-------------------------|
| 7.76 oz<br>0.22 kg | 12-24VAC/DC | 2.12 oz<br>0.06 kg | 4.23 oz<br>0.12 kg | 6.70 oz<br>0.19 kg | 5.29 oz<br>0.15 kg | 9.17 oz<br>0.26 kg    | 14.46 oz<br>0.41 kg     | 21.16 oz<br>0.60 kg     |
|                    | 120-240 VAC | —                  | 6.0 oz<br>0.17 kg  | 8.47 oz<br>0.24 kg | 6.70 oz<br>0.19 kg | 12.35 oz<br>0.35 kg   | 16.58 oz<br>0.47 kg     | 24.69 oz<br>0.70 kg     |

# StreamLine® Modular Electronic Sounder (SLM700)

## SPECIFICATIONS

Operating Temperature: -40°F to 131°F -40°C to 55°C



ACCESSORIES FOR DOCK BASE

















## HOW TO ORDER

- Specify model number:  
SLM700GY - Gray body  
SLM700R - Red body
- Specify required mounting base (see chart)
- Optional dome guard  
For shallow mounting base (SLMDG1)  
For deep mounting base (SLMDG2)
- Accessories for Twin and Wall Mount Bases  
Cable Gland, M20, Gray, 2 Pack (K77700416)  
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base  
1" NPT Adapter (SLMNPT1)  
1/2" NPT Adapter (SLMNPT2)
- Accessories for Dock Base  
Wall Mount Bracket (SLMB23W)  
1/2" NPT Adaptor (SLMB23N)  
Retaining Ring (SLM-RR)  
Light Visor (SLMB23V)

## MOUNTING BASE OPTIONS

Mounting bases are rated Type 4X. Final product rating is determined by top module. In combination with SLM700, the unit is Type 3R, IP65. For added protection, install with included retaining ring (SLM-RR).

|  |                     |                   |                |  |
|--|---------------------|-------------------|----------------|--|
|                        | <b>Model Number</b> | <b>Base Color</b> | <b>Voltage</b> |   |
|  | SLMBS-012-024GY     | Gray              | 12-24VAC/DC    |  |
|                       | SLMBS-012-024R      | Red               | 12-24VAC/DC    |  |
|  | SLMBD-012-024GY     | Gray              | 12-24VAC/DC    |  |
|  | SLMBD-012-024R      | Red               | 12-24VAC/DC    |  |
|  | SLMBD-120-240GY     | Gray              | 120-240VAC     |  |
|                       | SLMBD-120-240R      | Red               | 120-240VAC     |                  |
|  | SLMBW-012-024GY     | Gray              | 12-24VAC/DC    |  |
|                       | SLMBW-120-240GY     | Gray              | 120-240VAC     |                                    |
|  | SLMBP-012-024GY*    | Gray              | 12-24VAC/DC    |  |
|                       | SLMBP-120-240GY*    | Gray              | 120-240VAC     |                |
|  | SLMBT-012-024GY     | Gray              | 12-24VAC/DC    |  |
|                       | SLMBT-120-240GY     | Gray              | 120-240VAC     |                |
|  | SLMB2-024GY*        | Gray              | 24VAC/DC       |  |
|  | SLMB2-120-240GY*    | Gray              | 120-240VAC     |  |
|  | SLMB3-024GY*        | Gray              | 24VAC/DC       |  |
|                       | SLMB3-120-240GY*    | Gray              | 120-240VAC     |                             |
| Note: Dock bases allow one function per position and include visors. Dock bases are NPN compatible only. |                     |                   |                |  |

\*Installation of included retaining ring is required for pipe and dock bases.

Rev. B