

SELECT MODELS ARE DISCONTINUED

Effective immediately, the following models are discontinued and no longer available to order.

DISCONTINUED MODELS

DISCONTINUED MODEL	DESCRIPTION
110-154	Loudspeaker, 15 W, ISMT, Marine
114-754	Loudspeaker, 8 W, ISMT, EExdIIB
114-754-C-Q	Loudspeaker, 8 W, ISMT, EExdIIB, ceiling mount
141ST-240B	Electraflash, strobe, 240 Vac, blue
300SA	SelecTone® secondary amplifier
BPL26ST-B	Battery powered portable strobe warning light, 12 Vdc, blue
ES1-112-74	Loudspeaker, powered, 15 W, multi-voltage, ATEX, EExdIIB
ES1-112-7MT	Sounder, 15 W, multi-voltage, ATEX, EExdIIB
ES1-114-74	Loudspeaker, powered, 8 W, multi-voltage, ATEX, EExdIIB
FT100BW	Telephone, weatherproof, black
IS-CAREEX6T	Speaker, EEX, 6 W/8 W
LR100-AMP	Amplifier, 100 W
LR100-AMP-SB	Amplifier, CTA, 100 W
K8107213A	Lamp, 28 V, incandescent
K8107A149A	Lamp, 240 Vac, incandescent
K2005366A	PCBA, 24 V, 120-240 V, 15 W, ES1, MS1
K7002086A-16	Screw, cap, 15 W
K7067014A	O-Ring, 90 mm diameter, 110 Series, 114 Series, ES1, MS1
K8459130A	Plug, 1/2" NPT, 371BRCKT
K8597134A	Bracket, mounting, 110 Series, 114 Series, ES1, MS1
K8597198A	Kit, 15 W speaker fixing
K8597201A	O-Ring Kit, 15 W
K8476122A	Gasket, 50GC adapter
WCP-BG-DFL-10K-1K	ATEX Call Point, break glass, DIN rail, with lift flap and duty label, 10 K end of line resistor, 1 K series resistor

DISCONTINUED MODEL	DESCRIPTION
WCP-BG-DFL-3.3K-1.0K	ATEX Call Point, break glass, DIN rail, with lift flap and duty label, 3.3 K end of line resistor, 1 K series resistor
X-BBX6H	Backbox, six speaker, ceiling mount
X-BRG5	Tile bridge for five ceiling speakers
X-CELL10BDT-100	Speaker
X-PBC6T72	Speaker, cabinet, 70 V, 5 W, terminal block, ABS white

Please contact Tech Support at SignalSupport@fedsig.com for recommended substitutes based on application requirements.