

FB2LED FAMILY NOW AVAILABLE IN MAGENTA



FEATURES

- Available in 12-24 VDC or 120-240 VAC
- Available in Amber, Blue, Clear, Green, Magenta, and Red
- 50,000-hour LED
- Indoor or outdoor use
- Patented Power Select™ technology allows users to change flash patterns without opening the device

Federal Signal is pleased to announce that the FB2LED, FB2LEDX, and FB2LEDX-CN models are now available in Magenta. These models offer three user-selectable flash patterns (steady, 60 FPM, 120 FPM) and can be mounted easily on pipes or surfaces.

Units come pre-programmed to 60 FPM with the option to change flash patterns using Federal Signal's Power Select™ technology. This feature allows users to switch between flash patterns without the need to open the device, simply by following a sequence of applying power.

The housings are specifically designed to withstand corrosion, vibration, and water- and dust-ingress in challenging environments such as industrial warning, process control, status indication, and food processing. Safe area models are compliant with general UL signaling requirements, while hazardous location models meet UL division or zone ratings for the most demanding environments and include an added stainless steel wire guard for enhanced protection.

RATINGS AND CERTIFICATIONS

FB2LED	FB2LEDX	FB2LEDX-CN
Type 4X, IP66 enclosure	Type 4X, IP66 enclosure	Type 4X, IP66 enclosure
IP69K compliant	IP69K compliant	IP69K compliant
UL and cUL Listed	UL and cUL Listed for Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G; Class III	UL and cUL Listed for Class I, Zone 2, AEx nA IIC Gc; Class II, Zone 22 AEx tc IIIC Dc

HOW TO ORDER

MODEL	DESCRIPTION	UPC
FB2LED-012-024M	Fireball® LED Light, UL and cUL, 12-24 VDC, Magenta	782979100881
FB2LED-120-240M	Fireball LED Light, UL and cUL, 120-240 VAC, Magenta	782979100898
FB2LEDX-012-024M	Fireball Hazardous Location LED Warning Light, 12-24 VDC, Magenta	782979100904
FB2LEDX-120-240M	Fireball Hazardous Location LED Warning Light, 120-240 VAC, Magenta	782979100911
FB2LEDX-CN-012-024M	Fireball Hazardous Location LED Warning Light, C1Z2, 12-24 VDC, Magenta	782979100928
FB2LEDX-CN-120-240M	Fireball Hazardous Location LED Warning Light, C1Z2, 120-240 VAC, Magenta	782979100935